IN THE CLAIMS

Please cancel without prejudice claims 8, 11, 17, 22, 24-28, 36, 39, 44, and 47-49.

Please amend claims 1-2, 6-7, 9-10, 14, 18-19, 23, 29, 37-38, and 42 as indicated below.

- 1. (Currently Amended) A computer implemented method comprising:

 selecting an updated set of attributes in a routing table before selecting a set of updated

 destinations associated with the selected set of attributes;

 generating an update message that includes the set of updated destinations;

 selecting a dummy attribute before selecting a second set of updated destinations; and

 generating a second update message indicating the second set of updated destinations as

 unreachable.
- 2. (Currently Amended) The computer implemented method of claim 1 wherein the routing table includes a destination data structure and an attribute data structure, wherein the destination data structure that includes the set of updated destinations[[,]] and a set of path data structures, and <u>wherein</u> an attribute data structure that includes an entry indicating the updated set of attributes.
- 3. (Original) The computer implemented method of claim 2 wherein the destination data structure is a radix trie.
- 4. (Original) The computer implemented method of claim 2 wherein the destination data structure is a hash table.

- 5. (Original) The computer implemented method of claim 1 wherein the updated set of attributes reference the set of updated destinations.
- 6. (Currently Amended) The computer implemented method of claim 1 wherein the set of updated destinations is a linked list and the updated set of attributes reference the linked list's head.
- 7. (Currently Amended) The computer implemented method of claim 1 wherein the set of updated destinations is a linked list and the updated set of attributes reference the linked list's head and tail.
- 8. (Canceled)
- 9. (Currently Amended) A computer implemented method comprising:
 selecting a first data structure, the first data structure corresponding to a best path to a destination;
 - referencing a first element of a second data structure from the selected first data structure,

 the first element indicating a set of attributes of the best path; and

 referencing a second element of a third data structure from the first element, the second

 element indicating the destination;

determining a second destination to be unreachable; and

referencing a third element of the third data structure from a dummy element of the second data structure, the third element indicating the second destination.

10. (Currently Amended) The computer implemented method of claim 9 further comprising: selecting the first element in the second data structure; tracing a chain of elements of the third data structure from the selected first element; creating an update message, the network update message indicating the set of attributes;

indicating a set of destinations that are indicated by the chain of elements in the update

message; and

transmitting the network update message.

- 11. (Canceled)
- 12. (Original) The computer implemented method of claim 9 wherein the second data structure is a hash table.
- 13. (Original) The computer implemented method of claim 9 wherein the third data structure is a radix trie.
- 14. (Currently Amended) A network device comprising:
 - a memory to host a routing table, the routing table to include a first data structure to indicate a set of destinations and a second data structure to indicate a set of attributes; and
 - a set of one or more processors coupled with the memory, the set of processors to process

 a network update message that indicates one of the set of destinations and a subset

 of the set of attributes and to insert the one of the set of destinations into a chain

Application Serial No. 09/992,354

of elements of the first data structure in accordance with the network update message, the chain to be referenced by an element of the second data structure that indicates the subset of the set of attributes,

wherein the set of processors is to insert a second element of the first data structure into a second attribute-oriented chain that is referenced by a dummy element of the second data structure.

- 15. (Ciriginal) The network device of claim 14 wherein the first data structure is a radix trie.
- 16. (Criginal) The network device of claim 14 wherein the second data structure is a hash table.
- 17. (Canceled)
- 18. (Currently Amended) The network device of claim-14 further comprising

 A network device comprising:
 - a memory to host a routing table, the routing table to include a first data structure to indicate a set of destinations and a second data structure to indicate a set of attributes; and
 - a set of one or more processors coupled with the memory, the set of processors to process

 a network update message that indicates one of the set of destinations and a subset

 of the set of attributes and to insert the one of the set of destinations into a chain

 of elements of the first data structure in accordance with the network update

 message, the chain to be referenced by an element of the second data structure that

 indicates the subset of the set of attributes.

Application Serial No. 09/992,354

wherein the set of processors is to trace the attributed attribute-oriented chain of elements, to generate a second network update message, and to indicate a subset of the set of destinations in the second network update message, the subset of destinations indicated by the attribute-oriented chain of elements.

- 19. (Currently Amended) A network device comprising:
 - a line card to receive an update message that indicates a destination and a set of attributes; and
 - a control card coupled with the line card, the control card to host a routing table, the routing table to include a first data structure to indicate a set of destinations and a second data structure to indicate a plurality of attributes, the control card to process the update message and to insert the destinations into a chain of elements of the first data structure in accordance with the update message, the chain to be referenced by an element of the second data structure, the element of the second data structure to indicate the set of attributes.
 - wherein the line card is to receive an unreachability update message indicating a second destination, and wherein the control card is to process the unreachability update message, to select a second element of the first data structure that indicates the second destination and to insert the selected second element into a dummy attribute-oriented chain.
- 20. (Criginal) The network device of claim 19 wherein the first data structure is a radix trie.
- 21. (Criginal) The network device of claim 19 wherein the second data structure is a hash table.

Application Serial No. 09/992,354

-6-

Atty. Docket No. 004906.P088

22. (Canceled)

- 23. (Currently Amended) The network device of claim 19 further comprising
 - A network device comprising:
 - a line card to receive an update message that indicates a destination and a set of attributes;
 and
 - a control card coupled with the line card, the control card to host a routing table, the

 routing table to include a first data structure to indicate a set of destinations and a

 second data structure to indicate a plurality of attributes, the control card to

 process the update message and to insert the destinations into a chain of elements

 of the first data structure in accordance with the update message, the chain to be

 referenced by an element of the second data structure, the element of the second

 data structure to indicate the set of attributes.
 - wherein the control card is to trace the chain of elements, to generate a second network update message, and to indicate a subset of the set of destinations in the second network update message, the subset of destinations indicated by the chain of elements.
- 24. 28. (Canceled)
- 29. (Currently Amended) A machine readable medium, which when executed by a set of one or more processors, cause said set of processors to perform operations comprising:

selecting an updated set of attributes in a routing table before selecting a set of updated destinations associated with the selected set of attributes; and generating an update message that includes the set of updated destinations for the set of attributes;

selecting a dummy attribute before selecting a second set of updated destinations; and generating a second update message indicating the second set of updated destinations as unreachable.

- 30. (Original) The machine readable medium of claim 29 wherein the routing table includes a destination data structure that includes the set of updated destinations, a set of path data structures, and an attribute data structure that includes an entry indicating the updated set of attributes.
- 31. (Original) The machine readable medium of claim 30 wherein the destination data structure is a radix trie.
- 32. (Original) The machine readable medium of claim 30 wherein the destination data structure is a hash table.
- 33. (Original) The machine readable medium of claim 29 wherein the updated set of attributes reference the set of updated destinations.
- 34. (Original) The machine readable medium of claim 29 wherein the set of updated destinations is a linked list and the updated set of attributes reference the linked list's head.

35. (Criginal) The machine readable medium of claim 29 wherein the set of set of updated destinations is a linked list and the updated set of attributes reference the linked list's head and tail.

36. (Canceled)

37. (Currently Amended) A machine readable medium, which when executed by a set of one or more processors, cause said set of processors to perform operations comprising:

selecting a first data structure, the first data structure corresponding to a best path to a destination;

referencing a first element of a second data structure from the selected first data structure,
the first element indicating a set of attributes of the best path; and
referencing a second element of a third data structure from the first element, the second
element indicating the destination;

determining a second destination to be unreachable; and

referencing a third element of the third data structure from a dummy element of the second data structure, the third element indicating the second destination.

38. (Currently Amended) The machine readable medium of claim 37 further comprising: selecting the first element in the second data structure; tracing a chain of elements of the third data structure from the selected first element; creating an update message, the network update message indicating the set of attributes;

indicating a set of destinations that are indicated by the chain of elements in the update message; and

transmitting the network update message.

- 39. (Canceled)
- 40. (Criginal) The machine readable medium of claim 37 wherein the second data structure is a hash table.
- 41. (Criginal) The machine readable medium of claim 37 wherein the third data structure is a radix trie.
- 42. (Currently Amended) A machine readable medium, which when executed by a set of one or more processors, cause said set of processors to perform operations comprising:[[:]]

selecting an element of a first data structure that is marked, the element indicating a set of attributes;

creating a network update message;

indicating the set of attributes in the message; and

indicating a set of one or more destinations in the update message, the set of destinations indicated by a set of linked elements of a second data structure, the element of the first data structure referencing the set of linked elements;

determining a second destination to be unreachable; and

referencing a fourth element of the second data structure from a dummy element of the first data structure, the fourth element indicating the second destination.

- 43. (Original) The machine readable medium of claim 42 further comprising:
 - selecting a third data structure, the third data structure corresponding to a best path to a destination;
 - referencing a second element of the first data structure from the selected third data structure, the second element indicating a second set of attributes, the second set of attributes describing the best path; and
 - referencing a third element of the second data structure from the second element, the third element indicating the destination.
- 44. (Canceled)
- 45. (Original) The machine readable medium of claim 42 wherein the first data structure is a hash table.
- 46. (Original) The machine readable medium of claim 42 wherein the third data structure is a radix trie.
- 47. 49. (Canceled)